

# K-36CL

## Lancam System

- 1/3" D/N Lan Camera
- SONY CCD, 520TVL
- Mechanical IR Cut Filter
- M-PEG4 & M-JPEG Dual Mode



Specification	Description
<b>Video</b>	
CCD sensor	1/3" Sony Super HAD CCD
System	NTSC / PAL
Horizontal resolution	520 TV lines
Lens	C/CS mount
Auto Iris type	DC-iris
D/N	Mechanical IR Cut Filter (Auto / Manual / Schedule)
AWB range	2500K ~ 9500K
AES	1/60 (PAL 1/50) ~1/100,000 sec
Min. illumination	
Color	0.5 lux @ F1 .2
B/W	0.03 lux @ F1 .2
IR sensitivity	400~700nm
<b>Image</b>	
Compression	MJPEG / MPEG-4
Resolution	D1/ Half D1 / CIF and D1 / Half D1 / CIF
Frame rate	30 (25) / 24/15 fps, adjustable
Picture size (quality)	4~64KB and 64Kbps~8Mbps (Bit rate)
Configurations	Max AGC, Contrast, Brightness, Sharpness, Saturation, AWB, BLC, Flickerless, Mirror
Motion detection	Motion Detection (96 zones, 5 levels)
High speed shutter	1/1000 sec
Privacy masking	3 Areas
Time stamp	Time / Date / Title
<b>Audio</b>	
Built-in Microphone	μ Law, 8 kHz sample rate
<b>Network</b>	
Interface	Ethernet (RJ-45 wired, 10/100 base- TX), MDIX support
Protocols	TCP/IP, DHCP, HTTP, ICMP, UPnP, ARP DNS, DDNS, PPPoE FTP, SMTP
Throughput	Max. 2.0 MB/sec
<b>Software</b>	
Web browser	Microsoft IE 6.0 or above
PC	Free bundle IP-SURVEILLANCE supports 32CH recording
Development tools	ActiveX /HTTP-API/SDK
Security	Multiple level / Multiple users / IP Address filtering
<b>Connectors</b>	
Video output	1.0 Vpp, 75 ohm, composite, negative, BNCx1
Alarm I / O	1input / 1 output
Serial port	RS-485
SD card	Alarm and Scheduled recording / update
USB	Configuration / Update
Reset	Factory Default
<b>Others</b>	
LED indicator	Power / Network indicator
Firmware update	Upgrade via SD, USB, HTTP or FTP
Power requiremen	DC12V/POE
Operating Temperature	0°C~50°C
Dimensions	60 (W) x 45 (H) x94 (D) mm
Approvals	FCC, CE, RoHS
Accessories	Power adapter x 1, User manual x 1, IP-SURVEILLANCES software x 1, USB wire x 1