

K-37CL

Lancam System

- 1/3" Lan Camera
- SONY CCD, 520TVL
- H.264 & M-JPEG Dual Streamin



Specification	Description
Video	
CCD sensor	1/3" Sony Super HAD CCD
System	NTSC / PAL
Horizontal resolution	520 TV lines
Lens	C/CS mount
Auto Iris type	DC-iris
AWB range	2500K ~ 9500K
AES	1/60 (PAL 1/50) ~1/100,000 sec
Min. illumination	0.5 lux @ F1 .2
Image	
Compression	Simultaneous MJPEG & H.264
Resolution	D1/ Half D1 / CIF
Frame rate	30 (25) / 24/15 fps, adjustable
Picture size (quality)	4~64KB and 64Kbps~8Mbps (Bit rate)
Configurations	Max AGC, Contrast, Brightness, Sharpness, Saturation, AWB, BLC, Flickerless, Mirror
Motion detection	Motion Detection (96 zones, 5 levels)
High speed shutter	1/1000 sec
Privacy masking	3 Areas
Time stamp	Time / Date / Title
Audio	
input	Built-in Microphone
output	D-SUB
Network	
Interface	Ethernet (RJ-45 wired, 10/100 base-TX), MDIX support
Protocols	TCP/IP, DHCP, HTTP, ICMP, UPnP, ARP DNS, DDNS, PPPoE, FTP, SMTP
Throughput	Max. 1.2 MB/sec
Software	
Web browser	Microsoft IE 6.0 or above
PC	Free bundle IP-SURVEILLANCE supports 16CH recording
Development tools	ActiveX /HTTP-API/SDK
Security	Multiple level / Multiple users
Connectors	
Video output	1.0 Vpp, 75 ohm, composite, negative, BNCx1
D-SUB 9 Pin	Audio output / Alarm-in / Alarm-out/RS-232
Push-in connector	RS-485
SD card	Alarm and Scheduled recording / update
USB	1 .1 Slave for PnP Configuration and Update
Reset	Factory Default
Others	
LED indicator	Network indicator / Warning
Firmware update	Upgrade via SD, USB, HTTP or FTP
Power requiremen	DC12V(4W)
Operating Temperature	0°C~50°C
Dimensions	62 (W) x 50 (H) x95 (D) mm
Approvals	FCC, CE, RoHS
Accessories	Power adapter x 1, User manual x 1, IP-SURVEILLANCES software x 1, USB wire x 1