

K-71CL

Day/Night IR Network Camera

- MPEG4 / MJPEG Dual mode & Dual streaming
- 30FPS@720x480
- 2-way audio
- Digital I/O: 2 in/ 2 out
- 3GPP for monitoring via 3G mobile phone
- Free 36CH recording software



Specification	Description
Hardware	
CPU	ARM 9, 32 bit RISC
RAM	64MB
ROM	8MB
Image Sensor	1/3" Sony SuperHad CCD, 520 TV lines
Lens	Fixed Lens, Focal length 6 mm, F1.6
Sensitivity	0.05 lux
Day/ Night	Optional removable IR Cut Filter (ICR)
Lens Changeable	Yes, CS Mount
Support DC IRIS	Yes
Digital I/O	2 In / 2 Out
Video Out	1 Analog video out (BNC connector)
Audio In	Built-in microphone
Audio Out	1 Line out (RCA connector)
Power Supply	DC 12V, 1A
Dimensions	W58 x H65 x D131.5 mm
Network	
Ethernet	10/ 100 Base-T
Wireless (K-71WCL)	802.11b/g
WEP	64 / 128 bit
Network Protocol	HTTP, TCP/IP, RTP/RTSP, 3GPP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP
Client Requirements	
OS	Windows 2000, XP, 2003, IE6.0
Suggested	Intel-C 2.0G, RAM: 512MB, Graphic card: 64MB
System	
Video Resolution	NTSC: 720x480, 704x480, 352x240, 176x120 PAL: 720x576, 704x576, 352x288, 176x144
Compression Format	MPEG-4, MJPEG
Frame Rate	Up to 30 FPS
Video Bitrate Adjust	CBR, VBR
Dual Streaming	Yes
3GPP	Yes, Live view with 3G mobile phone
Motion Detection	Yes, 3 different areas
Pre/ Post Alarm	Yes, configurable
Security	Password protection
Connection	Up to 10 clients simultaneously
Firmware Upgrade	HTTP mode, remotely
Audio	Yes, 2-way
SD card management	
Recording Trigger	Motion Detection, Sensor In, IP Check, Network Disconnect
Video Format	AVI, JPEG
Video Playback	Yes
Delete Files	Yes