

K-73CF

80M IR Network Camera

- Day & night functionality for 24-hour surveillance
- IR distance up to 80 meters
- MPEG4 / MJPEG Dual mode & Dual streaming
- 2-way audio
- Digital I/O: 2 in/ 2 out
- 3GPP for monitoring via 3G mobile phone
- Free 36CH recording software



| Specification | Description |
|----------------------------|---|
| Hardware | |
| CPU | ARM 9, 32 bit RISC |
| RAM | 64MB |
| ROM | 8MB |
| Image Sensor | 1/3" Sony SuperHad CCD, 520 TV lines |
| Lens | Vari-focal 10 ~ 40 mm, F1.4 |
| Infrared LED | 850nm / 7 LED |
| IR Distance | 80 Meters |
| Sensitivity | Normal: 0.1 lux, IR On: 0 lux |
| Water Proof | IP-66 standard |
| Power Supply | K-73CF: AC 90V ~ 260V / K-73CF-1: Embedded PoE Splitter (IEEE 802.3af) |
| Dimensions | W170 x H280 x L470 mm |
| Network | |
| Ethernet | 10/ 100 Base-T |
| Network Protocol | HTTP, TCP/IP, RTP/RTSP, 3GPP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP |
| Client Requirements | |
| OS | Windows 2000, XP, 2003, IE6.0 |
| Suggested | Intel-C 2.0G, RAM: 512MB, Graphic card: 64MB |
| System | |
| Video Resolution | NTSC: 720x480, 704x480, 352x240, 176x120 PAL: 720x576, 704x576, 352x288, 176x144 |
| Compression Format | MPEG-4, MJPEG |
| Frame Rate | Up to 30 FPS |
| Video Bitrate Adjust | CBR, VBR |
| Dual Streaming | Yes |
| 3GPP | Yes, Live view with 3G mobile phone |
| Image Snapshot | Yes |
| Video Adjust | Brightness, Contrast, Saturation, Hue, AES, BLC, AGC |
| Motion Detection | Yes, 3 different areas |
| Pre/ Post Alarm | Yes, configurable |
| Security | Password protection |
| Connection | Up to 10 clients simultaneously |
| Firmware Upgrade | HTTP mode, remotely |
| Audio | Yes, 2-way |
| Event System | |
| Event Trigger | Motion Detection, Sensor In |
| Trigger Actions | Send Email, Send to FTP, Save to SD Card, Digital Out |
| SD Card Management | |
| Recording Trigger | Motion Detection, Sensor In, IP Check, Network Disconnect |
| Video Format | AVI, JPEG |
| Video Playback | Yes |
| Delete Files | Yes |