

K-76CL-1

CMOS Network Camera

- MPEG4 / MJPEG Dual mode & Dual streaming
- 30FPS@640x480
- 2-way audio
- Digital I/O: 2 In / 2 Out
- 3GPP for monitoring via 3G mobile phone
- Free 36CH recording software



Specifaition	Description
Hardware	
CPU	ARM 9, 32 bit RISC
RAM	64MB
ROM	8MB
Image Sensor	1/4" CMOS
Lens	Fixed lens, Focal length 4 mm, F2.0
Sensitivity	1 lux
Lens Changeable	Yes, CS Mount
Digital I/O	2 In / 2 Out
Audio In	Built-in microphone
Audio Out	1 Line out (RCA connector)
Power Supply	K-76CL: DC 12V, 1A / K-76CL-1: Embedded PoE Splitter (IEEE 802.3af)
Dimensions	W69 x H60 x D151 mm
Network	
Ethernet	10/ 100 Base-T
Network Protocol	HTTP, TCP/IP, RTP/RTSP, 3GPP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP
Client Requirements	
OS	Windows 2000, XP, 2003, IE6.0
Suggested	Intel-C 2.0G, RAM: 512MB, Graphic card: 64MB
System	
Video Resolution	640x480, 320x240,160x120
Compression Format	MPEG-4, MJPEG
Frame Rate	Up to 30 FPS
Video Bitrate Adjust	CBR, VBR
Dual Streaming	Yes
3GPP	Yes, Live view with 3G mobile phone
Motion Detection	Yes, 3 different areas
Image Snapshot	Yes
Video Adjust	Brightness, Contrast, Saturation, Hue, AES, BLC, AGC
Pre/ Post Alarm	Yes, configurable
Security	Password protection
Connection	Up to 10 clients simultaneously
Firmware Upgrade	HTTP mode, remotely
Audio	Yes, 2-way
Event System	
Event Trigger	Motion Detection, Sensor In, IP Check, Network Disconnect
Trigger Actions	Send Email, Send to FTP, Digital Out