

KD-65CHS

Outdoor High Speed Dome



| Specification | Description |
|------------------------|---|
| Image | 1/4" SONY Super HAD CCD |
| Definition | 480 TVL |
| Sensitivity | 0.9Lux |
| Zoom | 22X(Hitachi) |
| Electrical | |
| Power supply | AC 24±4V |
| Power consumption | 50W |
| Operational | |
| Receiver | Built-in |
| Motor | Stepping motor |
| Sync system | External/internal |
| Preset position | 128 presets, can be labeled with editable title |
| Alarm function | 7 alarm input/2 alarm output, support alarm action. |
| Pan rotation range | Continuously 360° |
| Manual pan speed | 0.4° - 320°/S |
| Auto pan scan | 355° programmable |
| Tilt rotation range | tilt 90°, with auto flip |
| Manual vertical speed | 0.4° - 150°/S |
| Preset time | <1 s |
| Communication | RS485-422,AD,BI-PHASS code, axis visual control |
| Baud rate (RS485) | 2400/4800/9600/19200bps |
| Environmental | |
| Operating temperature | -40°~ +60° |
| Environmental humidity | 0 ~ 95% (no condensation) |
| Protection grade | IP66, TVS1500w lightning proof & surge proof |
| Physical | |
| Dimension (mm) | Indoor: 300× 215mm Outdoor: 300× 231mm |
| Gross weight(kg) | 8.50Kg |