

KD-94CHS

Outdoor High Speed P/T/Z Dome

- Intelligent design, easy installation and maintenance
- Infrared night vision: ≤60m
- High die-cast aluminum casing, shock-proof, rust-proof
- Protection grade IP66, with wiper
- 360°continuously rotation, upward angle (+90°, -90°), no spot



Specification	Description
Image sensor	1/4" SONY Super HAD CCD
Lens	35X Zoom(Hitachi)
Horizontal Resolution	530 TVL
Minimum illumination	0.7(D) / 0.01(N) Lux
Power	
Power supply	AC24V
Consumption	A: With infrared: 45W
Function	
Pan rotation	360°continuously
Tilt rotation	Tilt 180°(↔ +/- 90°, with auto-flip)
Rotation speed	Pan 0.4~80°/S Tilt 0.4~60°/S
Preset position	128 preset, 4 tour, 4 patter, 4 scan
Monitor method	manual controlling /timing start-up setting
Infrared controlling	manual/Auto (will start-up according to the light)
Distance of infrared night-vision	≤60m
Wiper controlling	manual controlling
Communication	
Baud rate	2400/4800/9600/19200
Protocol	PELCO/KALATEL/BOSCH(PHILIPS)/DIAMOND/AD/SENSORNT/VIDO B02 and seventeen protocols
ID setting	0-255
Alarm function	
Alarm input/output	7 alarm input/2 alarm output
Alarm input action	preset/tour/scan/pattern
Alarm output status	ON/OFF
Alarm Priority	1-7alarm priority can be set
output temperature	-40°C~+60°C
Protection grade	IP66 TVS1500W lightningproof, surge proof
Gross weight	8.5kg
Dimension	411.4*210*256mm