

KG-31CF

Varifocal Color Dome Camera

- 1/3" Sony / Panasonic CCD
- Min. illumination of 0.5 Lux, F1.4
- Separated protecting glasses
- Avoiding light reflection or image gone blur
- Switch function adjustable
- AGC/BLC/FLC
- IP66
- Offering 2 different IR Angles
 - 4mm lens: 20° / 30° / 60°
 - 6mm / 8mm lens: 20° and 50°
- 28 LEDs, IR Distance 20meters
- Bracket Allowing a rotation of 180° vertically and around its axis 360°



Specification	Description
Pick up Element	SONY CCD
Number of Pixels	<NTSC> 510(H)× 492(V) <PAL> 512(H)× 582(V)
AES	ON
AGC	ON-OFF
APG	-
ATW	-
BLC	ON-OFF
FLC	ON-OFF
Sync. Mode	Internal Sync.
Scanning System	2:1 Interteface
Resolution	420 TV Lines
White Balance	More than 48dB
Gamma	0.45
Minimum illumination	0.5Lux,F 1.4(0 Lux with IR)
Horizontal Sync. Frequency	NTSC: 15.734 KHz PAL: 15.625KH
Video Output	1.0Vp-p. 75ohm
Power Source	DC 12V
Power Consumption	4.2 W
Infraead LED Quantity	28
Infraead Peak Wavelength	850nm
Infraead Radiant Distance	20 meters(at least)
Infraead IR Lux control	5 Lux IR ON
Operation Temp.	-10°C~ 60°C
Ingress Protection	IP66
Lens Amount	6.0mm Board Lens (Standard) 4.0mm/8.0mm/12.0mm Board Lens (Optional)
Shutter Control	NTSC: 1/60-1/100,000 Sec. PAL: 1/50~1/100.000 sec.
Dimension	68.5(o)×98(L) mm
Net Weight	0.30kg