

SG-35CB-3PE

Color Board Camera

SG35CB-1PE

- 1/3" Med-Res. Color Board Camera
- f9.0~22.0mm/F2.0 Auto Iris Lens



SG35CB-2PE

- 1/3" Med-Res. Color Board Camera
- f3.8~9.5mm/F1.2 Asphenicl Auto Iris Lens
- f2.5~6.0mm/F1.3 Asphenicl Auto Iris Lens

SG35CB-3PE

- 1/3" Color Metal Housing Camera



Specification

Item	Description					
	SG-35CB-1PE		SG-35CB-2PE		SG-35CB-3PE	
TV System	PAL	NTSC	PAL	NTSC	PAL	NTSC
Pick Up Element	1/3" SONY Super HAD CCD		1/3" Color CCD		1/3" SONY Color CCD	
Number Of Total Pixels	537(H) X 597(V)	537(H) X 505(V)	537(H) X 597(V)	537(H) X 505(V)	537(H) X 597(V)	537(H) X 505(V)
Resolution	420 TV Line					
Minimum Illumination	Internal					
Minimum Illumination	0.3Lux@F2.0		0.3Lux@F1.2		0.15Lux@F2.0	
Electronic Shutter Speed Mode	AES ON: 1/50(60)sec.~ 1/100,000sec. AES OFF: 1/50(60)sec.		Automatic, 1/50(60) sec.~100,000sec.		N/A	
Back Light Compensation	ON/ OFF(Switchable)					
F.L (Flickerless)	ON/ OFF (Switchable)					
Gain Control	ON/ OFF (Switchable)					
White Balance	ATW					
Signal to Noise Ratio	More Than 48dB (AGC off)					
Video Output	1Vp-p Composite / 75Ω					
Power Supply	DC12V					
Power Consumption	1.5W					
Board Lens	Standard:f3.6mm/F2.0 Option:f2.5, 2.9, 4.3, 6.0, 8.0, 12.0, 16.0mm		Broad Len: f3.6mm/F2.0 Option: f2.5, 2.9, 6.0, 8.0, 12.0, 16.0mm		Standard: f3.8mm~9.5mm/F1.2 Auto Iris Lens Option: f2.5mm~6.0mm/F1.3 Auto Iris Lens Option: f9mm~22.0mm/F1.6 Auto Iris Lens	
Operation Temperature	-10C~+50C					
Operation Humidity	RH85% or less					
Storage Temperature	-20C~+60C					
Dimensions	38 (V) X 38 (H) mm		47.6(V) x 53(H) x 30(L) mm		38(V) x 38(H) x 57(L) mm	
Weight	15g		150g		50g	