

SG-39CH-3E

Color Standard Camera

LEAD-FREE Soldering

- 1/3" Hi-Super HAD CCD
- Resolution: 540 TVL (SONY HQ1)
- Minimum Illumination 0.05 Lux @ F1.0
- Mechanical Focus Adjustment
- Built-in Integrated DSP
- Day/Night Function



*Standard packing does not include lens.

Specification	Description
TV System	PAL / NTSC
Sync. System	Internal / Line Lock
Image Sensor	SONY HQ1
Number of Total Pixels	PAL 752(H) x 582 (V) NTSC 811(H)x 508(V)
Resolution	540TVL
Minimum Illumination	0.05 Lux @ F1.0
S/N Ratio	50dB(AGC OFF)
Gamma Correction	0.45
Video Output	1.0Vp-p / 75ohm
Iris Control	Video/DC
Electronic Shutter Speed Mode	AES ON : 1/50 (60)sec.~1/100,000sec.AES OFF : 1/50(60)sec.
Auto White Balance	Yes
Auto IRIS Output	D4 IRIS Jack
Switch	Auto IRIS modes : DC / Video Sync System : Internal / Line Lock (L.L) Back Light Compensation : ON / OFF Auto Gain Control : AGC / S .AGC Flickerless Control : ON / OFF
Lens Mount	CS mount
Adjustment VR	L.L V-phase; DC Level
Power Supply	AC24V/DC12V; 90~260Vac
Power Consumption	AC24V/DC12V : 3.5W ; 90~260Vac : 4.5W
Operation Temp.	-10°C~50°C
Operation Humidity	Max : RH 85%
Storage Temp.	-20°C~60°C
Storage Humidity	Max:RH90%
Dimensions	60(W) x 49(H) x 99(D) mm
Weight	AC24V/DC12V : 250g 90~260Vac : 300g

