

SG-48CDV

Vandal Proof Dome Camera

Features

- 1/3" Med-Res. Color
- Built-in Varifocal Lens
- Water Resistance IP66



Specification

Item	Description
Image Sensor	1/3" Color CCD
Number of Total Pixels	NTSC 537(H) x505(V) PAL 537(H)x597(V)
Sync. Modes	Internal
Resolution	420TVL
Minimum Illumination	0.15 Lux @ F1.2
S/N Ratio	More than 48dB (AGC Off)
Automatic Gain control	ON/OFF (Switchable)
F.L (Flickerless)	ON/OFF (Switchable)
AES	ON/OFF (Switchable)
Back Light Compensation	ON/OFF (Switchable)
DC Level	The VR for adjusting the IRIS level of auto Iris lens
White Balance	AWB
Video Output	1Vp-p Composite / 75 ohm
Lens	f3.8mm~9.5mm / F1.2 Aspherical Auto Iris Lens (Standard)
	f2.5mm~6.0mm / F1.3 Aspherical Auto Iris Lens (Optional)
	f9mm~22.0mm / F2.0 Aut Iris Lens (Optional)
Power Supply	12 Vdc
Power Consumption	1.8W
Operating Temp.	-10C~+50C / RH 85% or less
Dimensions	118(DIA) x 96(H) mm
Weight	Camera 800g