

HQ1 Vandal Proof Dome Camera

Features

- 1/3" Hi-Res. Color
- SONY HQ1/ 540TVL
- Minimum Illumination:0.25Lux@F1.2
- Built-in Varifocal Lens
- AES/AGC/BLC/F.L Switchable
- Water Resistance IP66



*Wall bracket is optional.

Specification

Item	Description
Image Sensor	1/3" SONY Super HAD CCD
Number of Total Pixels	NTSC 811(H) x508(V) PAL 795(H)x596(V)
Sync. Modes	Internal
Resolution	540TVL
Minimum Illumination	0.25 Lux @ F1.2
S/N Ratio	More than 48 dB(AGC OFF)
Automatic Gain control	ON/OFF (Switchable)
F.L (Flickerless)	ON/OFF (Switchable)
AES	ON/OFF (Switchable)
Back Light Compensation	ON/OFF (Switchable)
DC Level	The VR for adjusting the IRIS level of auto Iris lens.
White Balance	AWB
Video Output	1Vp-p Composite / 75 ohm
Lens / Angle of View	f3.8mm~9.5mm / F1.2 Aspherical Lens (Standard), Auto Iris Lens/ 74.2~30.0
	f2.5mm~6.0mm / F1.3 Aspherical Lens (Optional), Auto Iris Lens/ 108.2~47.6
	f9mm~22.0mm / F2.0 Aspherical Lens (Optional), Auto Iris Lens/ 29.2~13.0
Lead Free	YES
Power Supply	12 Vdc
Power Consumption	2.3W
Operating Temp.	-10C~+50C
Dimensions	118(DIA) x 96(H) mm
Weight	Camera: 800g; Bracket:750g