

SG-59HCDV, 58CDV

Vandalproof Camera

SG-59HCDV

1/3" Super Hi-Res./ 540 TVL

SG-58CDV

1/3" Hi-Res./ 420 TVL

Features

- 0 Lux (IR LEDs on at 4 Lux)
- AGC/AWB
- Signal to Noise Ratio to 48dB
- Build in 12 IR LEDs
- Illuminating Distance to 15 M
- Vandalproof Design



Specification

Item	Description			
	SG59HCDV		SG58CDV	
TV System	PAL	NTSC	PAL	NTSC
Pick Up Element	1/3" SONY Color CCD			
Resolution	540 TV Line (HQ1)		420TVL	
Number Of Total Pixels	795 (H) X 596 (V)	811 (H) X 508 (V)	537 (H) X 597 (V)	537 (H) X 505 (V)
Synchronization Mode	Internal			
Scan System	2:1 Interlace			
Minimum Illumination	0.4 Lux @F 2.0(w/o IR), 0Lux (w/ IR) IR LED ON at 4Lux, controlled by a CDS Sensor			
Signal to Noise Ratio	More Than 48dB			
Electronic Shutter	Automatic, 1/60(1/50) ~ 1/100,000 SEC.			
Gamma Control	r=0.45			
Automatic Gain Control	Automatic			
White Balance	Automatic 2,500K~9,500K			
Video Output	1Vp-p Composite / 75Ω			
Case to take weight	10 pound			
IR LED	12Unit IR-LED/ Life: 6000 Hours.			
IR wavelength	850nm			
IR Working Distance	15M			
IR LED Power Switchable	CDS Auto Control			
Power Supply	DC12V+-10%			
Power Consumption	IR on:2.8W(230mA); IR off:1.2W(100mA)		IR on:3.4W(280mA); IR off:1.7W(140mA)	
Lens	Standard:4.3mm/F2.0 Board Lens ; Options:6.0mm/ 8.0mm/ 12mm F2.0			
Operating Temp.	-10C~+50C / RH85% or less			
Dimensions	108.5 (Dia) X 76.6 (H) mm			
Weight	420g			

Dimensions

