

SG38CDV-1, 2E

Color Dome Camera W/ Varifocal Lens

SG38CDV-1E

DC12V

SG38CDV-2E

AC24V / DC12V



Specification

Item	Description
Pick Up Element	1/3" Color CCD
Number Of Total Pixels	NTSC 537(H) X505 (V) PAL 537 (H) X 597 (V)
Synchronization Mode	Internal
Resolution	380 TV Line
Minimum Illumination	0.15Lux @F1.3 ; 0.2Lux @F1.6
Signal to Noise Ratio	More Than48dB (AGC OFF)
Gain Control	Automatic ON/OFF (switchable)
Flickerless	ON/OFF (switchable)
AES	ON/OFF (switchable)
B.L.C.	ON/OFF (switchable)
DC level	The VR for adjusting the IRIS level of auto iris lens
White Balance	2500o K~9200oK
Video Output	1Vp-p Composite / 75Ω
Lens	f3.8mm~9.5mm/F1.3 Aspherical Lens (Standard)
	f2.5~6mm / F1.6 ; f9~22mm / F2.0(Optionl)
Power Supply	12Vdc(Standard) 12Vdc/24Vac (Optional)
Power Consumption	1.8W
Operating Temperature	-10C~+50C/RH85% or less
Dimensions	118 (D) X 88 (H) mm
Weight	12Vdc:380g ; 12Vdc/24Vac : 450G